

OS		<ul style="list-style-type: none"> Telium TETRA 	✓
Processor	<ul style="list-style-type: none"> Application & Crypto processor 	<ul style="list-style-type: none"> Cortex 32bit – 160 Mhz 	✓
Memory	<ul style="list-style-type: none"> Internal 	<ul style="list-style-type: none"> 700 KB RAM, 2 MB Flash 	✓
Card readers	<ul style="list-style-type: none"> Magstripe Smart card Contactless 	<ul style="list-style-type: none"> ISO 1/2/3, 500K lifespan EMV Level 1, 500K lifespan EMV Contactless L1 3.0 certified 	<ul style="list-style-type: none"> ✓ ✓ ✓
Display	<ul style="list-style-type: none"> Colour 	<ul style="list-style-type: none"> 2.8" display, QVGA (320x240 pixels) – Glass lens 	✓
Keypad		<ul style="list-style-type: none"> 15 keys, raised marking, 4 function keys 	✓
Terminal connections	<ul style="list-style-type: none"> USB 	<ul style="list-style-type: none"> 1 USB Host 	✓

Audio	<ul style="list-style-type: none"> Buzzer 		✓
Terminal size		<ul style="list-style-type: none"> 180.2x83.2x43 mm (7.08x3.26x1.69") 	✓
Weight		<ul style="list-style-type: none"> 221 g (7.79oz) 	✓
Environment	<ul style="list-style-type: none"> Operating Temperature Storage Temperature Operating Humidity 	<ul style="list-style-type: none"> 0°C to +40°C (32°F to 104°F) -20°C to +55°C (-4°F to 131°F) 85% non-condensing at +40°C (104°F) 	<ul style="list-style-type: none"> ✓ ✓ ✓
Accessory	<ul style="list-style-type: none"> Privacy shield 	<ul style="list-style-type: none"> Factory mounted Field upgradable 	Option Option
Security		<ul style="list-style-type: none"> PCI PTS 6.x online & offline certified 	✓