

OS		<ul style="list-style-type: none"> • Telium TETRA
Memory	<ul style="list-style-type: none"> • Internal 	<ul style="list-style-type: none"> • 256 MB Flash, 256 MB RAM
Processor	<ul style="list-style-type: none"> • Application & Crypto processor 	<ul style="list-style-type: none"> • Cortex A7
Card readers	<ul style="list-style-type: none"> • Magnetic card reader • Smart Card • Contactless 	<ul style="list-style-type: none"> • ISO 1/2/3, 500K reads lifespan • EMV L1, 500K reads lifespan • EMV Contactless L1 3.0 certified
Display		<ul style="list-style-type: none"> • 2.8"backlight, glass lens, QVGA (320x240 pixels)
Keypad	<ul style="list-style-type: none"> • Physical keys 	<ul style="list-style-type: none"> • 15 keys, raised markings, backlit • 4 function keys
Audio	<ul style="list-style-type: none"> • Buzzer 	
Thermal printer	<ul style="list-style-type: none"> • Speed in l/s • Paper roll cage 	<ul style="list-style-type: none"> • up to 24 l/s • 58 mm width x Ø 40 mm
Terminal Connections	<ul style="list-style-type: none"> • USB 	<ul style="list-style-type: none"> • USB-C
Terminal Connections via Accessories	<ul style="list-style-type: none"> • Magic Box 	<ul style="list-style-type: none"> • Ethernet, 1 USB(slave), 2 USB(host)
Terminal Size	<ul style="list-style-type: none"> • Terminal full option without PINshield 	<ul style="list-style-type: none"> • 179x77.4x55 mm (7.04x3.05x2.16")
Terminal Weight	<ul style="list-style-type: none"> • Terminal only 	<ul style="list-style-type: none"> • 285g (10.05oz)
Environment	<ul style="list-style-type: none"> • Operating temperature • Storage temperature • Relative humidity 	<ul style="list-style-type: none"> • 0 to +45°C (32°F to 113°F) • -20 to +50°C (-4°F to 122°F) • 85% HR at +40°C (104°F)
Security	<ul style="list-style-type: none"> • PCI PTS 	<ul style="list-style-type: none"> • PCI PTS V6 certified